# Safety data sheet (SDS)

Date of Issue 2024/11/27

1 Product and company identification

Product name Ferrite magnet Size Any sizes

Company name Niigata Seiki Co., Ltd.

5-3-14 Tsukanome, Sanjo-city, Niigata-pref. Japan zip 955-0033 Add.:

Telephone 0256-33-5502 Facsimile 0256-33-5528

2. Hazards identification

**[GHS classification]** 

Classification name Not classified as hazardous materials

CAS NO. Not applicable Official gazette reference No. Not applicable UN classification and nos. Not applicable

3 Composition/Information on ingredients

[Chemical character]

Strontium ferrite oxide compound Chemical state Strontium oxide Composition Iron oxide others 1%

SrO · 6Fe<sub>2</sub>O<sub>3</sub>

No plated for standard product Plate composition

JP official gazette reference No. Nο UN classification and UN Nos. Nο

Chemical formula and structure

4. First aid measure

If inhalation N/A under normal conditions of use. But if you feel sick when inhaling dust occurred by

processing, move to fresh air and keep at rest in comfortable position for breathing.

If skin N/A under normal conditions of use. But if molten, cool immediately in clean water,

treat as ordinary burns. Under normal conditions of user, wash water with soap.

If in Eyes If you get a foreign objects (debris or dust) in your eyes, immediate rinse eyes with

clean water. Do not rub eyes.

If there is a sensation of foreign matter, rinse the eyes thoroughly until the sensation

disappears, and get medical attention immediately.

If swallowed If debris or dust is swallowed, induce vomiting by drinking water.

Get medical attention if you feel unwell.

5 Firefighting measures

Suitable extinguishing media Water, powder extinguish agent, carbon dioxide gas, dry sand.

Unsuitable extinguishing media Not applicable

6 Accidental release measures

mend and emergency procedures

Personal precautions, protective equip- To avoid the high risk of magnetic field, magnets may affect the normal operation of

implanted electronic medical devices, such as pacemakers.

Environmental precautions Collect in a sealable container and dispose of container as industrial waste.

Dispose of powder, powder, dust, etc. according to No. 13 Disposal conditions as

described below.

Methods and materials for containment No special treatment required for solid state. If spilled, collect in container

and cleaning up.

However, fine powder generated by processing, etc. should be removed with adequate

ventilation and wearing protective equipment to avoid inhalation.

7 Handling and storage

[Precautions for safe handling]

Exposure control measures for Wear protective equipment such as long sleeves, long pants, and protective gloves

during use or process if necessary.

Provide adequate ventilation to prevent inhalation of fumes during the process. Personal handling

Do not place magnetic products such as magnetic cards or tape near this product

fire and explosion prevention

Suitable technical measures, including Keep away from fire and other ignition sources.

## Safety data sheet (SDS)

[Storage precautions]

Incompatible chemical materials No data

Storage conditions Avoiding direct sunlight and long-term storage in high temperature and humidity.

(Conditions for safe storage, including

any incompatibilities)

Store away from heat and ignition sources

### 8 Exposure controls and personal protection

[Exposure control]

Exposure limits Not established Tolerable Concentrations of Not established biological indicators

Suitable protective equipments Long sleeves, long pants, gloves etc., should be used for protection during processing,

if necessary.

### 9 Physical and chemical properties

[Individual protection measures]

[Appearance]

Physical condition Solid-state under general conditions

Form Round, Ring, Square

Color Silver
Odor Odorless
Freezing point boiling point and range No data

melting point and

Flash point, auto ignition temperature No data
Flammability upper and lower limit No data
Vapor pressure/density No data
Specific gravity (relative density) 5.0g/cm3
Solubility No data

[Others]

Reaction with water Oxidizable Oxidizing Yes

### 10 Stability and reactivity

[Conditions to avoid]

Electrostatic discharge Stable under normal condition of use and storage.

Shock · Vibration Avoiding for brittle

[Incompatible materials]No data[Hazardous decomposition materials]No data

#### 11 Toxicological information

Acute toxicity No data

Skin corrosiveness and irritation Friction causes loss of sebum on the fingers and turns to red chafing.

Serious eye damage or irritation No data
Respiratory or skin sensitization No data
Germ cell mutagenicity No data
Carcinogenic No data
Reproductive toxicity No data
Specific target organ toxicity Single exp No data
Specific target organ toxicity repeat exp No data
Absorption respiratory organs toxicity No data

#### 12 Ecological information

Ecotoxicity No data
Persistence and degradability No data
Bioaccumulative No data
Mobility in soil No data
Hazards to ozone layer No data

#### 13 Disposal considerations

[Safe and environmentally suitable

disposal method]

[Proper disposal of container and

In accordance with the law (Waste Disposal and Public Cleansing Law), consign disposal to an industrial waste disposal company licensed by the prefecture.

Proper containers and packaging should be used in accordance with the instructions

# Safety data sheet (SDS)

Packaging of the industrial waste disposal contractor.

14 Transport information

[Code international transport regulations and classification]
HS code 8505.11

Others Load the cargo without tipping over or falling. Take preventive measures to prevent

injuries due to collapses etc. Avoiding rough handling as it is easily crack

15 Regulatory information

Substance to be notify for Industrial N/A

safety and health law

Substance to be labeled for Industrial N/A

safety and health law

Poisonous and deleterious substances N/A

control law

Pollutant Release and Transfer Register N/A

law (PRTR)

Waste disposal and public cleaning law Other local ordinances to be followed

16 Other information

Magnetic leakage precautions for

air-transport cargo.

For General cargo transport, Does not exceed 0.418A/m (0.00525 gauss) or, Compass deflection of 2 degrees or less at a distance of 2.1m from appointed point. (In case e entire inside of the packaging of the magnet or magnetembedded product is surrounded by a steel plate (0.5 mm or thicker) with no gaps)

3