Safety data sheet (SDS)

Date of Issue 2024/11/27

1 Product and company identification

Product name Ferrite magnet Size Any sizes

Company name Niigata Seiki Co., Ltd.

Add.: 1-22-17 Hayashicho, Sanjo-city, Niigata-pref. Japan zip 955-0061

Telephone 0256-33-5501 Facsimile 0256-33-5551

2. Hazards identification

【GHS classification】

Classification name Not classified as hazardous materials

CAS NO. Not applicable
Official gazette reference No. Not applicable
UN classification and nos. Not applicable

3 Composition/Information on ingredients

[Chemical character]

Chemical state Strontium ferrite oxide compound
Composition Strontium oxide 10%
Iron oxide 89%
others 1%

Chemical formula and structure SrO • 6Fe₂O₃

Plate composition No plated for standard product

JP official gazette reference No. No UN classification and UN Nos. No

4. First aid measure

If skin

If inhalation N/A under normal conditions of use. But if you feel sick when inhaling dust occurred by

processing, move to fresh air and keep at rest in comfortable position for breathing. N/A under normal conditions of use. But if molten, cool immediately in clean water,

troat as ordinary hurns. Under normal conditions of user, wash water with soan

treat as ordinary burns. Under normal conditions of user, wash water with soap.

If you get a foreign objects (debris or dust) in your eyes, immediate rinse eyes with

clean water. Do not rub eyes.

If there is a sensation of foreign matter, rinse the eyes thoroughly until the sensation

disappears, and get medical attention immediately.

If swallowed, induce vomiting by drinking water.

Get medical attention if you feel unwell.

5 Firefighting measures

Suitable extinguishing media Water, powder extinguish agent, carbon dioxide gas, dry sand.

Unsuitable extinguishing media Not applicable

6 Accidental release measures

Personal precautions, protective equip-To avoid the high risk of magnetic field, magnets may affect the normal operation of

mend and emergency procedures implanted electronic medical devices, such as pacemakers.

Environmental precautions Collect in a sealable container and dispose of container as industrial waste.

Dispose of powder, powder, dust, etc. according to No. 13 Disposal conditions as

described below.

Methods and materials for containment No special treatment required for solid state. If spilled, collect in container

and cleaning up. However, fine powder generated by processing, etc. should be removed with adequate

ventilation and wearing protective equipment to avoid inhalation.

7 Handling and storage

(Precautions for safe handling)

Exposure control measures for Wear protective equipment such as long sleeves, long pants, and protective gloves

during use or process if necessary.

Personal handling Provide adequate ventilation to prevent inhalation of fumes during the process.

Do not place magnetic products such as magnetic cards or tape near this product

Suitable technical measures, including Keep away from fire and other ignition sources.

fire and explosion prevention

(Storage precautions)

Incompatible chemical materials No data

Storage conditions Avoiding direct sunlight and long-term storage in high temperature and humidity.

(Conditions for safe storage, including Store away from heat and ignition sources

any incompatibilities)

8 Exposure controls and personal protection

[Exposure control]

Exposure limits Not established Tolerable Concentrations of Not established

biological indicators

[Individual protection measures]

Suitable protective equipments Long sleeves, long pants, gloves etc., should be used for protection during processing,

if necessary.

9 Physical and chemical properties

[Appearance]

Physical condition Solid-state under general conditions

Form Round, Ring, Square

Color Silver
Odor Odorless
Freezing point boiling point and range No data

melting point and

Flash point, auto ignition temperature No data Flammability upper and lower limit No data Vapor pressure/density No data Specific gravity (relative density) 5.0g/cm3 Solubility No data

(Others)

Reaction with water Oxidizable
Oxidizing Yes

10 Stability and reactivity

[Conditions to avoid]

Electrostatic discharge Stable under normal condition of use and storage.

Shock · Vibration Avoiding for brittle

[Incompatible materials] No data[Hazardous decomposition materials] No data

11 Toxicological information

Acute toxicity No data

Skin corrosiveness and irritation Friction causes loss of sebum on the fingers and turns to red chafing.

Serious eye damage or irritation No data
Respiratory or skin sensitization No data
Germ cell mutagenicity No data
Carcinogenic No data
Reproductive toxicity No data
Specific target organ toxicity Single ext No data
Specific target organ toxicity repeat ext No data
Absorption respiratory organs toxicity No data

12 Ecological information

Ecotoxicity No data
Persistence and degradability No data
Bioaccumulative No data
Mobility in soil No data
Hazards to ozone layer No data

13 Disposal considerations

[Safe and environmentally suitable disposal method]

(Proper disposal of container and Packaging]

In accordance with the law (Waste Disposal and Public Cleansing Law), consign disposal to an industrial waste disposal company licensed by the prefecture. Proper containers and packaging should be used in accordance with the instructions of the industrial waste disposal contractor.

14 Transport information

[Code international transport regulations and classification]

HS code 8505.11

Others Load the cargo without tipping over or falling. Take preventive measures to prevent

injuries due to collapses etc. Avoiding rough handling as it is easily crack

15 Regulatory information

Substance to be notify for Industrial

safety and health law

N/A

Substance to be labeled for Industrial N/A

safety and health law

Poisonous and deleterious substances N/A

control law

Pollutant Release and Transfer Register N/A

law (PRTR)

Waste disposal and public cleaning law Other local ordinances to be followed

16 Other information

Magnetic leakage precautions for air-transport cargo.

For General cargo transport, Does not exceed 0.418A/m (0.00525 gauss) or, Compass deflection of 2 degrees or less at a distance of 2.1m from appointed point. (In case e entire inside of the packaging of the magnet or magnetembedded product is surrounded by a steel plate (0.5 mm or thicker) with no gaps)